



- 01 Bluetooth®:** Allows up to 10 m wireless range for easy programming and remote control
- 02 Battery-Operated:** Includes two durable AA alkaline batteries to last a full season
- 03 Cycling Mode:** Optimal for interval drip system irrigation or for germinating plant seeds

BTT BLUETOOTH TAP TIMER

Automatically irrigate gardens, plants, and flowers from a hose faucet

BTT provides efficient light irrigation to even the smallest landscapes. BTT is easy to operate and simple to set up, and is designed for use with a hose faucet. It gives users convenient options to remotely program irrigation from their smartphone, and avoid climbing around shrubs or stepping on delicate plants to operate. BTT includes long-lasting batteries, and uses a mobile iOS® or Android™ app with two irrigation modes and two start times each to program watering schedules. The built-in, push-button manual start allows up to one hour of manual irrigation with automatic shutoff, without the need for a smartphone.

BTT makes simple irrigation quick and affordable, and is the perfect add-on item for contractors to offer additional service and easy maintenance.



Haji Sons International
Authorized Distributor
IRRIGATION LANDSCAPING SOLAR SYSTEM LASER LAND LEVELER SEEDS

Office : 72-B Gulberg II Lahore - Pakistan UAN : +92 42 111 474 474 , Mob : +92 300 8711434
Email : info@hsinternational.pk Website : www.hsinternational.pk

Learn more. Visit hunterindustries.com for more detailed information.

BTT FEATURES & SPECIFICATIONS

Features

- Bluetooth-enabled programming for easy wireless smartphone control
- Manage unlimited number of devices
- Multi-language mobile app
- Independent Timer and Cycling modes
- 6- and 24-hour maximum run times
- 7-Day Rain Delay period
- Manual push-button operation
- Automatic water shutoff after 1 hour
- Red LED low-battery indicator
- Secure passcode protection
- Rugged screen filter
- Includes quick coupler adapter
- Drip system ready with optional BTT-LOC
- Alkaline batteries included
- Warranty period: 2 years

Electrical Specifications

- Power: Requires two AA (1.5V) alkaline batteries (included)
- Communication: Bluetooth 4.0, BLE Module
- Operating temperature: 5° to 60°C

Operating Specifications

- Flow rate: 0.031 to 57 LPM (1.9 to 3,407 LPH)
- Recommended pressure: 0.5-8 bar (50-800 kPa)

App Specifications

- iOS 9.0 or above
- Android 4.4 or above
- Optimal communication distance: 3-5 m
- Maximum communication distance: 10 m

Model

BTT-101

Inlet diameter: 2.5 cm & 2 cm

Outlet diameter: 2 cm

Height: 13 cm

Width: 12 cm

Depth: 2 cm



Quick Coupler Adapter* (Included)

Inlet diameter: 2 cm

Outlet diameter: 1.6 cm

Height: 3.8 cm

Width: 3.3 cm



*Included with BTT-101

BTT-LOC (Optional)

Inlet diameter: 2 cm

Outlet diameter: 16-18 mm drip tube

Height: 7 cm

Width: 3 cm



The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG Inc. and any use of such marks by Hunter Industries is under license. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. Android is a trademark of Google LLC.



Website hunterindustries.com | **Customer Support** +1760-752-6037 | **Technical Service** +1760-591-7383

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.


Gregory R. Hunter, CEO of Hunter Industries

BTT

Take advantage of smartphone-controlled, above-ground irrigation for easier access to the hose tap.

KEY BENEFITS

- Number of zones:
 - 1 or 2
- Battery-operated tap timer with Bluetooth® control
- 1 smartphone manages an unlimited number of controllers
- 1-second to 24-hour run time with 4 start times for maximum programming flexibility
- Cycling mode repeats continuously within user-defined water windows, perfect for drip systems or germinating seeds
- Suspend irrigation up to 99 days during the off-season, perfect for seasonal markets
- Manual push-button operation for quick operation without a smartphone
- Automatic water shutoff after 1 hour prevents water waste
- Blinking LED low-battery alert indicates battery replacement
- Secure passcode protection prevents unauthorized schedule changes
- Alkaline batteries included for quicker installation

OPERATING SPECIFICATIONS

- Two 1.5V AA alkaline batteries (included)
- BTT-100 flow rate: 5 to 17 GPM (60 to 1,000 GPH)
- BTT-200 flow rate: 4 to 15 GPM (48 to 900 GPH)
- Recommended pressure: 7 to 116 PSI
- Approvals: Plastic IPX6, Bluetooth 4.2 BLE, UL, cUL, FCC, CE, RCM
- Warranty period: 2 years

APP SPECIFICATIONS

- iOS® 9.0 or above
- Android™ 4.4 or above
- Maximum communication distance: 32'



BTT-100
Inlet diameter: 3/4"
Outlet diameter: 3/4"
Height: 5"
Width: 4 9/10"
Depth: 2 3/8"



BTT-200
Inlet diameter: 3/4"
Outlet diameter: 3/4"
Height: 6 1/8"
Width: 5 3/10"
Depth: 3"



BTT-LOC
(optional)
Inlet diameter: 3/4"
Outlet diameter: 16-18 mm dripline
Height: 2 3/4"
Width: 1 1/4"



Pressure Regulator
(optional)
Inlet diameter: 3/4"
Outlet diameter: 3/4"
Height: 3"
Width: 1 1/2"

BTT	
Model	Description
BTT-100	1-zone Bluetooth Tap Timer, 3/4" hose thread
BTT-200	2-zone Bluetooth Tap Timer, 3/4" hose thread
BTT-LOC	BTT adapter for 16-18 mm dripline

PRESSURE REGULATOR	
Model	Description
PRLG203FH3MH	20 PSI pressure regulator, 3/4" hose thread
PRLG253FH3MH	25 PSI pressure regulator, 3/4" hose thread
PRLG303FH3MH	30 PSI pressure regulator, 3/4" hose thread
PRLG403FH3MH	40 PSI pressure regulator, 3/4" hose thread

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG Inc. and any use of such marks by Hunter Industries is under license. iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. Android is a trademark of Google LLC.

BTT

