

# PRS40

To optimize MP Rotator performance, the Pro-Spray PRS40 is pressure-regulated to 40 PSI.

## KEY BENEFITS

- Industry's strongest spray body for years of reliable performance
- Pressure-regulated to 40 PSI for the MP Rotator
- Gray cap for easy field identification
- Co-molded wiper seal made from chemical- and chlorine-resistant materials
- Innovative seal design prevents cap-to-body leaks, even with a loose cap
- FloGuard technology option eliminates water waste in the event of a missing nozzle

## ADDITIONAL FEATURES

- Directional flush plug design for cleaner installation
- Interchangeable components for easier servicing, retrofits, and upgrades
- Heavy-duty spring for consistent riser retraction
- Check valve option eliminates low-head drainage

## OPERATING SPECIFICATIONS

- Operational pressure range: 15 to 100 PSI
- Warranty period: 5 years

## FACTORY-INSTALLED OPTIONS

- Check valve available for 4", 6", and 12" models (up to 14' of elevation)
- Reclaimed water identification
- FloGuard technology available for pop-up models

## USER-INSTALLED OPTIONS

- Check valve (up to 14' of elevation; P/N 437400SP)
- Reclaimed water ID cap (P/N 458562SP)
- Snap-on reclaimed cover (P/N PROS-RC-CAP-SP)
- Shutoff cap (P/N 213600SP)
- Shutoff nozzle (P/N 916400SP)



### PRS40 Reclaimed

PRS40 models include optional factory-installed purple reclaimed caps



**PROS-00-PRS40**  
Retracted height: 4¾"  
Inlet size: ½"



**PROS-04-PRS40-CV**  
Retracted height: 5½"  
Pop-up height: 4"  
Exposed diameter: 2¼"  
Inlet size: ½"



**FloGuard Technology**



**PROS-06-PRS40-CV**  
Retracted height: 8¾"  
Pop-up height: 6"  
Exposed diameter: 2¼"  
Inlet size: ½"



**PROS-12-PRS40-CV**  
Retracted height: 16½"  
Pop-up height: 12"  
Exposed diameter: 2¼"  
Inlet size: ½"

## PRO-SPRAY PRS40 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Feature Options	3 Specialty Options
<b>PROS-00-PRS40</b> = 40 PSI regulated shrub adapter <b>PROS-04-PRS40</b> = 40 PSI regulated 4" pop-up <b>PROS-06-PRS40</b> = 40 PSI regulated 6" pop-up <b>PROS-12-PRS40</b> = 40 PSI regulated 12" pop-up	<b>(blank)</b> = No option <b>CV</b> = Factory-installed drain check valve (Pop-up models only)	<b>(blank)</b> = No option <b>R</b> = Factory-installed reclaimed body cap <b>F</b> = FloGuard technology <b>F-R</b> = FloGuard technology with reclaimed body cap

## PRO-SPRAY PRS40 (SIDE INLET) MODELS

### Model

**PROS-06-SI-PRS40** = 40 PSI regulated 6" pop-up with side inlet

**PROS-12-SI-PRS40** = 40 PSI regulated 12" pop-up with side inlet

### Examples:

**PROS-06-SI-PRS40** = 6" pop-up with side inlet regulated at 40 PSI  
**PROS-06-PRS40-CV** = 6" pop-up regulated at 40 PSI, drain check valve  
**PROS-12-PRS40-CV-F-R** = 12" pop-up regulated at 40 PSI, drain check valve, and FloGuard technology with reclaimed body cap

Compatible with:



MP Rotator



# HAJI SONS INTERNATIONAL

IRRIGATION LANDSCAPING SOLAR SYSTEM LASER LAND LEVELER SEEDS

Authorized Distributor

Office : 72-B Gulberg II Lahore - Pakistan  
 Email : info@hsinternational.pk

UAN : +92 42 111 474 474 , Mob : +92 300 8711434  
 Website : www.hsinternational.pk