



- 01 **Reliable:** Commercial controller construction that's built to last with up to 54 stations
- 02 **Powerful:** Packed full of features you expect from Hunter with 4 programs (up to 2 simultaneous), 8 start times per program, and up to 12 hours run times
- 03 **Flexible:** Easy to program and to install, using proven modular expansion with enhanced surge protection

ICC IS BACK BY POPULAR DEMAND

Hunter's classic ICC commercial controller led the industry for more than a decade with its simplicity, reliability, and power in a super competitive package. Now it's back with enhancements that will catch your eye, not hurt your wallet. ICC2 builds on its predecessor's legacy by enhancing surge protection, increasing station count, and adding a large backlit display. The new facepack and modules are even backward compatible to keep older ICC systems operational for years to come.

ICC2 can also host the EZ Decoder System (EZDS) for powerful and affordable two-wire control. Configure up to 54 stations with EZ-1 decoders or a combination of two-wire and conventional output modules.



Haji Sons International

IRRIGATION LANDSCAPING SOLAR SYSTEM LASER LAND LEVELER SEEDS

Authorized Distributor

Office : 72-B Gulberg II Lahore - Pakistan
Email : info@hsinternational.pk

UAN : +92 42 111 474 474 , Mob : +92 300 8711434
Website : www.hsinternational.pk

ICC2 CONTROLLER FEATURES & SPECIFICATIONS

This reliable control system can run conventional, two-wire, or hybrid operations with the option to upgrade to Centralus™ cloud-based control.

KEY BENEFITS

- Number of stations:
 - Conventional: 8 to 38 (plastic), 8 to 54 (metal and pedestals)
 - With two-wire EZDS: up to 54 (all enclosure options)
- 4 independent irrigation programs (8 start times each) allow for customized scheduling
- 12-hour maximum station run time provides flexibility for low-flow zones
- Any 2 programs can operate simultaneously, providing more efficient watering
- 1 sensor input available for use with Solar Sync® or any Klik sensors
- 1 P/MV output for pump start relay and master valve activation
- Backward compatibility to original ICC controllers allows for quick updates to older systems
- Upgradeable to Centralus software for web-based central control options

OPERATING SPECIFICATIONS

- Transformer input: 120/230 VAC
- Transformer output (24 VAC): 1.4 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.56 A
- Approvals: Wall Mounts IP44, Plastic Pedestal IP34, NEMA 3R, UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- WIFIKIT or LANKIT communications for Centralus web-based control
- Compatible with Flow-Klik® sensor for catastrophic high-flow shutdown

ICC2	
Model	Description
I2C-800-PL	8-station base model, plastic outdoor wall mount
I2C-800-M	8-station base model, gray metal outdoor, wall mount
I2C-800-SS	8-station base model, stainless steel, wall mount
I2C-800-PP	8-station base model, plastic pedestal
ICC-FPUP2	ICC2 retrofit kit for original ICC controllers
ICC-PED	Gray pedestal for metal wall mount
ICC-PED-SS	Stainless steel pedestal for stainless wall mount
ICC-PWB	Optional pedestal wiring board for metal pedestals

ICC2 SERIES STATION EXPANSION	
Model	Description
ICM-400	4-station plug-in module with enhanced surge suppression
ICM-800	8-station plug-in module with enhanced surge suppression
ICM-2200	22-station expansion module (one per controller)
EZ-DM	54-station decoder output module (one per controller)
EZ-1	Single-station EZ decoder



Plastic
Height: 12"
Width: 13¾"
Depth: 5"

Metal
(gray or stainless steel)
Height: 16"
Width: 13"
Depth: 5"



Metal Pedestal
(gray or stainless steel)
Height: 36"
Width: 11½"
Depth: 5"



Plastic Pedestal
Height: 39"
Width: 24"
Depth: 17"


Compatible with:



**Solar Sync
Sensor**



**ROAM Remote
ROAM XL Remote**



**EZ Decoder
System**



EPA WaterSense

Add the WaterSense-labeled Solar Sync sensor to improve the water efficiency of this controller.

Website hunterindustries.com | **Customer Support** 1-800-383-4747 | **Technical Service** 1-800-733-2823

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

Gene Smith

Gene Smith, President, Landscape Irrigation and Outdoor Lighting

ICC2

This reliable control system can run conventional, two-wire, or hybrid operations with the option to upgrade to Centralus™ cloud-based control.

KEY BENEFITS

- Number of stations:
 - Conventional: 8 to 38 (plastic), 8 to 54 (metal and pedestal)
 - With two-wire EZDS: up to 54 (all enclosure options)
- 4 independent irrigation programs (8 start times each) allow for customised scheduling
- 12-hour maximum station run time provides flexibility for low-flow zones
- Any 2 programs can operate simultaneously, providing more efficient watering
- 1 sensor input available for use with Solar Sync™ or any Clik sensors
- 1 P/MV output for pump start relay and master valve activation
- Backward compatibility to original ICC controllers allows for quick updates to older systems
- Upgradeable to Centralus software for web-based central control options

OPERATING SPECIFICATIONS

- Transformer input: 120/230 VAC
- Transformer output (24 VAC): 1.4 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.56 A
- Approvals: Wall Mounts IP44, Plastic Pedestal IP34, NEMA 3R, UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- WIFIKIT or LANKIT communications for Centralus web-based control
- Compatible with Flow-Clik™ sensor for catastrophic high-flow shutdown

ICC2	
Model	Description
I2C-800-PL	8-station base model, plastic outdoor wall mount
I2C-800-M	8-station base model, grey metal outdoor, wall mount
I2C-800-SS	8-station base model, stainless steel, wall mount
I2C-800-PP	8-station base model, plastic pedestal
ICC-FPUP2	ICC2 retrofit kit for original ICC controllers
ICC-PED	Grey pedestal for metal wall mount
ICC-PED-SS	Stainless steel pedestal for stainless wall mount
ICC-PWB	Optional pedestal wiring board for metal pedestals

ICC2 SERIES STATION EXPANSION

Model	Description
ICM-400	4-station plug-in module with enhanced surge suppression
ICM-800	8-station plug-in module with enhanced surge suppression
ICM-2200	22-station expansion module (one per controller)
EZ-DM	54-station decoder output module (one per controller)
EZ-1	Single-station EZ decoder



Plastic

Height: 30.5 cm
Width: 35 cm
Depth: 12.7 cm

Metal

(grey or stainless steel)
Height: 40.6 cm
Width: 33 cm
Depth: 12.7 cm



Metal Pedestal

(grey or stainless steel)
Height: 91.4 cm
Width: 29.2 cm
Depth: 12.7 cm



Plastic Pedestal

Height: 99 cm
Width: 61 cm
Depth: 43 cm


Compatible with:



**Solar Sync
Sensor**
Page 146



ROAM Remote
Page 137
ROAM XL Remote
Page 138



**EZ Decoder
System**
Page 134



Smart WaterMark

Recognised as a responsible water-saving tool when used with a Solar Sync sensor